



Page No:1/5

This form has been prepared according to regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204).

PERMOLIT PERULO AKRİLİK TEXTURE DIŞ CEPHE KAPLAMASI / PERULO ACRYLIC TEXTURED EXTERIOR COATING

Form No : GBF 03.013 Revision No : 2	Revision Date : 05.06.2017 Revision No : 2	: 01.11.2007 : GBF 03.013	· · · · · · · · · · · · · · · · · · ·
--------------------------------------	---	------------------------------	---------------------------------------

1. Identification of the Substance/Mixture and of the Company/Undertaking

1.1. Product identifier

Permolit Perulo Acrylic Textured Exterior Coating

1.2. Relevant identified uses of the mixture and uses advised against Water based, top coat, rough, textured exterior coating

1.3. Details of the supplier of the safety data sheet

Name	: Akçalı Boya ve Kimya San. Tic. A.Ş.
Address	: Osmangazi M. Mareşal Fevzi Çakmak C. No:5 Esenyurt – İstanbul / Türkiye
Tel / Fax	: +90 0212 886 23 43 (Pbx) / +90 0212 886 18 11
Contact e-mail	: zekir.senol@akcaliboya.com.tr

1.4. Emergency telephone number

Emergency telephone number	: +90 212 886 23 43
National Toxic Consultation Center	: 114 (UZEM)

2. Hazards Identification

2.1. Classification of the substance/mixture

Classification according to regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures and Turkish regulation R.G. 11.12.2013-No: 28848 (repeating):

The product hasn't been classified.

2.2. Label elements

Labelling isn't required.

EUH 208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (Cas No: 55965-84-9). May produce an allergic reaction.

Precautionary Statements

P102	: Keep out of reach of children.
P262	: Do not get in eyes, on skin, or on clothing.
P270	: Do not eat, drink or smoke when using this product.
P273	: Avoid release to the environment.
P302+P352	: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P33	8 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
lenses, if present	and easy to do. Continue rinsing.

2.3. Other hazards

It has not been classified to according to PBT and vPvB.

3. Composition/Information on the Ingredients

3.2. Mixture



Page No:2/5

This form has been prepared according to regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204).

PERMOLIT PERULO AKRİLİK TEXTURE DIŞ CEPHE KAPLAMASI / PERULO ACRYLIC TEXTURED EXTERIOR COATING

Preparation Date	: 01.11.2007	Revision Date	: 05.06.2017
Form No	: GBF 03.013	Revision No	· 2
FUIII NO	. GDF 03.013	Revision No	. 2

Ingredient name	EC No	CAS No	%	Classification (EC 1272/2008)
Kerosine (petroleum), hydrodesulfurized;	265-184-9	64742-81-0	1-2	GHS08; Asp. Tox. 1-H304
Ethylene glycol	203-473-3	107-21-1	<1	GHS07; Acute Tox. 4 *-H302
reaction mass of: 5- chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1)		55965-84-9	<0,0015	GHS06; Acute Tox. 3 *-H331 Acute Tox. 3 *-H311 Acute Tox. 3 *-H301 GHS05; Skin Corr. 1B-H314 GHS07; Skin Sens. 1-H317 GHS09; Aquatic Acute 1-H400 Aquatic Chronic 1-H410

*For the explanation of the listed hazard statements refer to Section 16.

4. First Aid Measures

4.1 Description of first aid measures

Inhalation : Remove to fresh air. In case of persistent complaints obtain medical attention.

Ingestion : Do not induce vomiting. Immediately obtain medical attention.

Skin contact: Remove contaminated clothing. Clean the skin with water, soap and special cleaning cream.

Eye contact : Flush eye with copious quantities of water. If irritation occurs, obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Other information is not available.

4.3 Indication of any immediate medical attention and special treatment needed

Other information is not available.

5. Firefighting Measures

The product isn't flammable.

5.1 Extinguishing media

```
Suitable extinguishing media : Water, dry chemical powder, foam, CO<sub>2</sub>, inert absorbent sand. : No
```

5.2 Special hazards arising from the substance or mixture

- If fire starts, not breathe the fume
- 5.3 Advice for firefighters

Use suitable protective clothes, boots, gloves, eye and face protective, breathing equipment.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

If leak and spilt occurs, ventilate the environment sufficiently, wear personal protective equipment.

6.2 Environmental precautions

Keep away from drains, surface and ground water and soil.



Page No:3/5

This form has been prepared according to regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204).

PERMOLIT PERULO AKRİLİK TEXTURE DIŞ CEPHE KAPLAMASI / PERULO ACRYLIC TEXTURED EXTERIOR COATING

Form No : GBF 03.013 Revision No : 2	Preparation Date Form No		Revision Date Revision No	: 05.06.2017 : 2	
--------------------------------------	-----------------------------	--	------------------------------	---------------------	--

6.3 Methods and material for containment and cleaning up

Use sand, sawdust or inert absorbent material to limit product leakage. Transfer the leaky material to suitable containers for safe disposal. Soak up with an appropriate absorbent material and put it in a closed container for safe disposal in accordance with current legislation (Section 13).

6.4 Reference to other sections

Responding to accident place, wear personal protective equipment in Section 8 and dispose of waste in accordance with procedure in Section 13.

7. Handling and Storage

7.1 Precautions for safe handling

Use in well-ventilated areas. Extra special precautions aren't required. Avoid product releasing unrestrainedly.

7.2 Conditions for safe storage, including any incompatibilities

Store in closed package at ambient temperature protecting from direct sun lights and hot. Product isn't flammable and explosive.

7.3 Specific end use(s)

Use by looking product label.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Indicative occupational exposure limit values:

Ingredient name	TWA-8 h	ours	STEL-15	minutes	Notation
Ethylene glycol Cas No:107-21-1	52 mg/m ³	20 ppm	104 mg/m ³	40 ppm	Skin

8.2 Exposure controls

Personal protective equipment

Respiratory protection	: Special equipment isn't required. Provide ventilation in working area.
Hand protection	: Wear waterproof rubber gloves with CE marking.
Eye protection	: Use eyewear with CE marking.
Skin protection	: Not require special clothes. Take off working-clothes after usage.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	: Liquid
Colour	: Card colours
Odour	: Special characteristic odour
Viscosity	: 180 ± 10 KU (25°C)
-	195 ± 10 KU (25°C)
Density	: 1,75 ± 0,15 gr/cm ³ (25°C)
Solid	$: 76 \pm 2 (120^{\circ}C 30 min)$
рН	: 8,5 ± 1
Flash point	: Not applicable
Self igniting	: Product is not self igniting
Boiling point	: Not determined
Melting point	: Not determined





Page No:4/5

This form has been prepared according to regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204).

PERMOLIT PERULO AKRİLİK TEXTURE DIŞ CEPHE KAPLAMASI / PERULO ACRYLIC TEXTURED EXTERIOR COATING

Preparation Date Form No	: 01.11.2007 : GBF 03.013	Revision Revision		: 05.06.2017 : 2
Solubility VOC *ready to use	: Soluble in water : < 40 g/L*			
9.2 Other inform Other information				
10.4 Conditions 10.5 Incompatib	tability of hazardous reactions to avoid le materials	 : Under normal conditions, product : Stable under normal conditions of : Not : Not special conditions. : Not special materials. : No hazardous decomposition product 	of storage	e and use.
	on toxicological effects re available for the produc : Not detect our : Not detect : Not detect : Not detect	:. ed a problem. ed a problem. ed a problem. se irritation eyes.		
12.1 Toxicity 12.2 Persistence 12.3 Bioaccumul 12.4 Mobility in s	ta are available for the pro- and degradability ative potential oil BT and vPvB assessmen	 Not dangerous for environment. No available data No bioaccumulative potential for p No mobility 	product	

13. Disposal Considerations

Disposal of waste/surplus and contaminated packaging should be carried out in accordance with applicable regional, national and local laws and regulations. According to Turkish regulation of Waste Management (R.G. 02.04.2015 No: 29314), waste codes:

Waste paint and varnish : 080111 Contaminated package : 150110 Contaminated waste : 150202

13.1 Waste treatment methods

Do not allow product to reach sewage system. Wastes should be sent to licensed recycling facility

14. Transport Information

Road Transport: ADR / RID ve GGVS / GGVEMarine Transport: IMDG / GGVSeaAir Transport: ICAO - TI ve IATA DGRProduct isn't dangerous goods according to these regulations.



This form has been prepared according to regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204).

PERMOLIT PERULO AKRİLİK TEXTURE DIŞ CEPHE KAPLAMASI / PERULO ACRYLIC TEXTURED EXTERIOR COATING

Preparation Date : 01.11.2007	Revision Date	: 05.06.2017	
Form No : GBF 03.013	Revision No	: 2	

14.1 UN number

14.2 UN proper shipping name	: Not applicable.	
14.3 Transport hazard class(es)	: Not applicable.	
14.4 Packing group	: Not applicable.	
14.5 Environmental hazards	: Not applicable.	
14.6 Special precautions for user	: Not applicable	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable		

Not applicable

15. Regulatory Information

The product has been classified and marked according to Globally Harmonized System (GHS).

Regulation EC No 1272/2008 of the European Parliament and of the Council 16 December 2008 on Classification, Labelling and Packaging of Substances and Mixtures and Turkish Regulation about Classification, Labelling and Packaging of Substances and Mixtures-R.G. 11.12.2013-No: 28848 (repeating),

Regulation (EC) No 453/2010 and regulation on Material Safety Data Sheet related to Hazardous Substances and Mixtures (R.G. 13.12.2014-29204),

This form has been prepared according to regulations above.

Indicative occupational exposure limit values have been written in accordance with Directive 98/24/EC and Turkish regulation Health and Safety Precautions on Working with Chemical Material 12.08.2013-28733.

16. Other Information

Revision has been carried out due to regulation change.

Explanation of the hazard and precautionary statements according to (EC) No 1272/2008 and Turkish regulation R.G. 11.12.2013-No: 28848 (repeating):

Hazard Statements

- H301 : Toxic if swallowed
- H302 : Harmful if swallowed
- H304 : May be fatal if swallowed and enters airways
- H311 : Toxic in contact with skin
- H314 : Causes severe skin burns and eye damage
- H317 : May cause an allergic skin reaction
- H331 : Toxic if inhaled.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.

Name-Surname	: Zekir ŞENOL
MSDS Certificate No	: GBF – 1904
Document Date	: 13.04.2015

Not : The data given here is based on our current knowledge and experience. The purpose of this safety data sheet is to describe the products in terms of their safety requirements. However, it shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.