

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 1/17 Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Safety Data Sheet Complies with Annex II of REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

AKCALI SPRAY SYNTHETIC FLORESAN PAINT Product name

UFI: 6KV0-E02T-6001-0ME2

CODE: 6723.081.S513-S516-S519-S521-S522-S524-S533

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Spray painting product.

Identified Uses	Industrial	Professional	Consumer
Spray paint based on acrylic resins in the solvent phase	-	~	~
Uses Advised Against			

Uses other than those recommended

1.3. Information on the supplier of the safety data sheet

Company Name

AKÇALI BOYA VE KİMYA SAN. TİC. A.Ş. OSMANGAZİ MAH. MAREŞAL FEVZİ ÇAKMAK CAD. NO: 5 Address

ESENYURT / İSTANBUL **Location and Country**

TURKEY

Tel: +90-212-8862343 Fax: +90-212-8861811

E-mail address of the authorized person:

Responsible for the safety data sheet zekir.senol@akcaliboya.com.tr

Placing on the market responsible entity AKÇALI BOYA VE KİMYA SAN. TİC. A.Ş.

1.4. Emergency telephone number For emergency information, consult:

Turkey: +90 212 886 23 43 (08:00 - 17:00 / Monday - Friday) National Toxic Consultation Center (Turkey): 114 (UZEM)

Telephone numbers of the main poison control centers in Germany (available 24/7):

Poison Control Center of Charité Universitätsmedizin - Berlin; Tel. 030 - 192 40

Information Center Against Poisoning - Bonn; Tel. 0228 - 192 40 - Tel. 0228 - 287 334 80 Poison Control Center - Erfurt; Tel. 0361 - 730 730

Poison Information Center - Freiburg; Tel. 0761 - 192 40

Poison Information Center North for the Länder of Bremen, Hamburg, Lower Saxony and Schleswig-Holstein (GIZNord); Tel. 0551 - 192 40 Poison Information Center for the Länder of Rhineland-Palatinate and Hesse - Mainz; Tel. 06131 - 192 40 - Tel. 06131 - 232 466

Poison Control Center Munich - Munich - Tel. 089 - 192 40

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 2/17

Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1 H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures above 50°C / 122°F.

P501 Dispose of the product / container in accordance with local regulations.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P211 Do not spray on an open flame or other ignition source.

Contains: ACETONE

Revision No: 4 Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 3/17 Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

XYLENE, MIXTURE OF ISOMERS

VOC (Directive 2004/42/EC):

Special finishes - All types.

VOC given in g/litre of product in a ready-to-use condition : 622,50 Limit value: 840,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ACETONE		
INDEX 606-001-00-8	$24 \le x < 39$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-211947133049		
XYLENE, MIXTURE OF ISOMERS		
INDEX 601-022-00-9	10 ≤ x < 25	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l
CAS 1330-20-7		
REACH Reg. 01-2119488216-32		
PROPANE		
INDEX 601-003-00-5	9 ≤ x < 24	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		,
CAS 74-98-6		
BUTANE		
INDEX 601-004-00-0	7 ≤ x < 9	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7	Author vite the GET Progulation. 6, 6	
CAS 106-97-8		
ISOBUTANE		
INDEX 601-004-00-0	5 ≤ x < 7	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 4/17

Replaced Revision: 3

081 K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

EC 200-857-2 CAS 75-28-5

DIMETHYL CARBONATE

INDEX 607-013-00-6

 $1 \le x < 3$

Flam. Liq. 2 H225

EC 210-478-4 CAS 616-38-6

REACH Reg. 01-2119548399-23-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 32,00 %

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further

contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, contact a POISON CENTER / doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

Revision No: 4

Revision Date: 04/02/2025

Printed on: 24/04/2025 Page No: 5/17

Replaced Revision: 3

081 K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 6/17

Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung Deutschland gesundheitsschädlicher Arbeitsstoffe Mitteilung 58 EST Eesti Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]
Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 FRA France décembre 2021 Decreto Legislativo 9 Aprile 2008, n.81 Italia POL Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie Polska w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea ROU România și completarea hotărârii guvernului nr. 1.093/2006 SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 - ZVZD-1, 38/15, 78/18 in 78/19) Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733; TUR Türkiye GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/183; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive EU OEL EU 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2023

Threshold Limit						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	1200	500	2400	1000	
MAK	DEU	1200	500	2400	1000	
TLV	EST	1210	500			
VLEP	FRA	1210	500	2420	1000	
VLEP	ITA	1210	500			
NDS/NDSCh	POL	600		1800		
TLV	ROU	1210	500			
MV	SVN	1210	500	2420	1000	
ESD	TUR	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	
Predicted no-effect	concentration - PNE	С				
Normal value in fres	sh water			10,6	mg/l	
Normal value in ma	rine water			1,06	mg/l	

Revision No: 4

Revision Date: 04/02/2025

Printed on: 24/04/2025

Page No: 7/17

Replaced Revision: 3

Normal value for fresh water sediment	30,4	mg/kg	
Normal value for marine water sediment	3,04	mg/kg	
Normal value for water, intermittent release	21	mg/l	
Normal value of STP microorganisms	100	mg/l	
Normal value for the terrestrial compartment	33,3	mg/kg	_

Health - Derived no-ef	fect level - DNEL / D Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg				·
Inhalation			VND	200 mg/m3	VND	2420 mg/m3	VND	1210 mg/m3
Skin			VND	62 mg/kg			VND	186 mg/kg

Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	1800	1000	7200	4000		
MAK	DEU	1800	1000	7200	4000		
TLV	EST	1800	1000				
NDS/NDSCh	POL	1800					
TLV	ROU	1400	778	1800	1000		
MV	SVN	1800	1000	7200	4000		
ESD	TUR	1800	1000				

XYLENE, MIXTURE OF ISOMERS

į	Threshold Limit \	/alue						
ſ	Туре	Country	TWA/8h		STEL/15min		Remarks /	
Į							Observations	
١			mg/m3	ppm	mg/m3	ppm		
Ì	TLV-ACGIH		434	0	0	0		

BUTANE							
Threshold Limit							
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
AGW	DEU	2400	1000	9600	4000		
MAK	DEU	2400	1000	9600	4000		
TLV	EST	1500	800				
VLEP	FRA	1900	800				
NDS/NDSCh	POL	1900		3000			
MV	SVN	2400	1000	9600	4000		
WEL	GBR	1450	600	1810	750		
WEL	GBR		4			RESP	
TLV-ACGIH					1000		

Legend:

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 8/17
Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Information

Appearance aerosol

Colour according to the range
Odour characteristic of solvent

Melting point / freezing point not available Initial boiling point not applicable Flammability flammable gas Lower explosive limit not available Upper explosive limit not available Flash point not applicable Auto-ignition temperature not available

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 9/17

Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Decomposition temperature not available

H not applicable Reason for missing data:substance/mixture is

non-polar/aprotic (eg: an organic solvent

Remark:(The product is a blend)

mixture)

Kinematic viscosity not available Solubility not available

Partition coefficient: n-octanol/water not applicable

Vapour pressure not available

Density and/or relative density not available

Relative vapour density not available

Relative vapour density not available
Particle characteristics not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC):

VOC (volatile carbon) 0,18 % - 1,32 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride,2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

10.4. Conditions to avoid

Avoid overheating.

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 10/17
Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

ACETONE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE

Incompatible with: acids,oxidising substances.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes, irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:

ATE (Inhalation - gas) of the mixture:

ATE (Inhalation - gas) of the mixture:

ATE (Oral) of the mixture:

ATE (Dermal) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

Not classified (no significant component)

ACETONE

 LD50 (Dermal):
 > 15800 mg/kg Coniglio

 LD50 (Oral):
 5800 mg/kg Ratto

 LC50 (Inhalation vapours):
 76 mg/l/4h Ratto

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 11/17
Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

XYLENE, MIXTURE OF ISOMERS

ATE (Dermal): LD50 (Oral): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) $\,$

5000 mg/kg

DIMETHYL CARBONATE

LD50 (Dermal): LD50 (Oral): > 5000 mg/kg Coniglio 13000 mg/kg Ratto

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 12/17 Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

12.1. Toxicity

Information not available

12.2. Persistence and degradability

BUTANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

PROPÁNE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable ACETÓNE

Rapidly degradable 12.3. Bioaccumulative potential

BUTANE

Partition coefficient: n-octanol/water 1,09

PROPANE

Partition coefficient: n-octanol/water 1,09

ACETONE

Partition coefficient: n-octanol/water -0,23 3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025 Page No: 13/17

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Replaced Revision: 3

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1950

14.2. UN proper shipping name

ADR / RID: **AEROSOLS** IMDG: **AEROSOLS**

IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --I imited Tunnel Quantities: 1 restriction

Special provision: 190, 327, 344, 625

IMDG: EMS: F-D, S-U

Limited Quantities: 1 code: (D)

Revision No: 4

Revision Date: 04/02/2025

Printed on: 24/04/2025

Page No: 14/17

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Replaced Revision: 3

IATA:	Cargo:	Maximum quantity: 150	Packaging instructions:
	December	kg Maximum	203
	Passengers:	Maximum quantity: 75	Packaging instructions:
		kg	203
	Special provision:	A145, A167,	

A802

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025 Page No: 15/17

Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Special finishes - All types.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ACETONE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A Flammable gas, category 1A

Aerosol 1 Aerosol, category 1
Aerosol, category 3

Flam. Liq. 2 Flammable liquid, category 2
Flam. Liq. 3 Flammable liquid, category 3

Press. Gas (Liq.) Liquefied gas

Acute Tox. 4 Acute toxicity, category 4

Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229Pressurized container: may burst if heated.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)

Revision No: 4

Revision Date: 04/02/2025

Printed on: 24/04/2025

Page No: 16/17 Replaced Revision: 3

081 K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- · VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
 Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Revision No: 4

Revision Date: 04/02/2025 Printed on: 24/04/2025

Page No: 17/17 Replaced Revision: 3

081_K - AKCALI SPRAY SYNTHETIC FLORESAN PAINT

Note for users:

thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.
CALCULATION METHODS FOR CLASSIFICATION Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9. Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11. Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.
Changes to previous review: The following sections were modified: 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.