

**AKCALI BOYA VE KİMYA SANAYİ TİCARET A.Ş.**

Revision No: 4
Revision Date: 01/02/2023
Printed on: 24/04/2025
Page No: 1/17
Replaced Revision: 3

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT

Safety Data Sheet

Complies with Annex II of REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT**
UFI : **76X0-106C-000F-K3G9**
CODE: **6723.083.S902-S910**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Spray painting product.**

Identified Uses	Industrial	Professional	Consumer
Spray paint based on acrylic resins in the solvent phase	-	✓	✓

Uses Advised Against

Uses other than those recommended

1.3. Information on the supplier of the safety data sheet

Company Name AKÇALI BOYA VE KİMYA SAN. TİC. A.Ş.
Address OSMANGAZI MAH. MAREŞAL FEVZİ ÇAKMAK CAD. NO: 5
Location and Country ESENYURT / İSTANBUL
TURKEY
Tel: +90-212-8862343
Fax: +90-212-8861811

E-mail address of the authorized person:
Responsible for the safety data sheet zekir.senol@akcaliboya.com.tr

Placing on the market responsible entity AKÇALI BOYA VE KİMYA SAN. TİC. A.Ş.

1.4. Emergency telephone number
For emergency information, consult:

Turkey: +90 212 886 23 43 (08:00 – 17:00 / Monday - Friday)
National Toxic Consultation Center (Turkey): 114 (UZEM)

Telephone numbers of the main poison control centers in Germany (available 24/7):

Poison Control Center of Charité Universitätsmedizin - Berlin; Tel. 030 - 192 40
Information Center Against Poisoning - Bonn; Tel. 0228 - 192 40 - Tel. 0228 - 287 334 80
Poison Control Center - Erfurt; Tel. 0361 - 730 730
Poison Information Center - Freiburg; Tel. 0761 - 192 40
Poison Information Center North for the Länder of Bremen, Hamburg, Lower Saxony and Schleswig-Holstein (GIZNord); Tel. 0551 - 192 40
Poison Information Center for the Länder of Rhineland-Palatinate and Hesse - Mainz; Tel. 06131 - 192 40 - Tel. 06131 - 232 466
Poison Control Center Munich - Munich - Tel. 089 - 192 40

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.

Revision No: 4

Revision Date: 01/02/2023

Printed on: 24/04/2025

Page No: 2/17

Replaced Revision: 3

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT

supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurized container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures above 50°C / 122°F.
P501	Dispose of the product / container in accordance with local regulations.
P102	Keep out of reach of children.
P211	Do not spray on an open flame or other ignition source.
P271	Use only outdoors or in a well-ventilated area.

Contains: ACETONE

VOC (Directive 2004/42/EC):

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.		Revision No: 4
		Revision Date: 01/02/2023
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT		Printed on: 24/04/2025
		Page No: 3/17
		Replaced Revision: 3
Special finishes - All types.		
VOC given in g/litre of product in a ready-to-use condition :		0,00
Limit value:		840,00
2.3. Other hazards		
On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.		
The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.		
SECTION 3. Composition/information on ingredients		
3.1. Substances		
Information not relevant		
3.2. Mixtures		
Contains:		
Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ACETONE		
CAS 67-64-1	$20 \leq x < 35$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
INDEX 606-001-00-8		
REACH Reg. 01-2119471330-XX		
PROPANE		
CAS 74-98-6	$9 \leq x < 24$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
BUTANE		
CAS 106-97-8	$9 \leq x < 24$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 203-448-7		
INDEX 601-004-00-0		
XYLENE, MIXTURE OF ISOMERS		
CAS 1330-20-7	$10 \leq x < 25$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C ATE Dermal: 1100 mg/kg, ATE Inhalation mists/powders: 1,5 mg/l
EC 215-535-7		
INDEX 601-022-00-9		
REACH Reg. 01-2119488216-32		
ISOBUTANE		
CAS 75-28-5	$7 \leq x < 9$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C, U
EC 200-857-2		
INDEX 601-004-00-0		

<p align="center">AKCALI BOYA VE KIMYA SANAYI TICARET A.S.</p>	<p>Revision No: 4 Revision Date: 01/02/2023</p>
<p align="center">083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT</p>	<p>Printed on: 24/04/2025 Page No: 4/17 Replaced Revision: 3</p>
<p>DIMETHYL CARBONATE</p> <p>CAS 616-38-6 5 ≤ x < 7 Flam. Liq. 2 H225</p> <p>EC 210-478-4</p> <p>INDEX 607-013-00-6</p> <p>REACH Reg. 01-2119548399-23-XXXX</p> <p>The full wording of hazard (H) phrases is given in section 16 of the sheet.</p> <p>The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.</p> <p>Percentage of propellants: 37,25 %</p> <p>SECTION 4. First aid measures</p> <p>4.1. Description of first aid measures</p> <p>EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice. SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again. INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately. INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.</p> <p>4.2. Most important symptoms and effects, both acute and delayed</p> <p>Specific information on symptoms and effects caused by the product are unknown.</p> <p>4.3. Indication of any immediate medical attention and special treatment needed</p> <p>Information not available</p> <p>SECTION 5. Firefighting measures</p> <p>5.1. Extinguishing media</p> <p>SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.</p> <p>5.2. Special hazards arising from the substance or mixture</p> <p>HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.</p> <p>5.3. Advice for firefighters</p> <p>GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.</p>	

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory references:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.					Revision No: 4			
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT					Revision Date: 01/02/2023			
					Printed on: 24/04/2025			
					Page No: 6/17			
					Replaced Revision: 3			
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006 Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 — ZVZD-1, 38/15, 78/18 in 78/19) Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733 EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2022						
ROU	România							
SVN	Slovenija							
TUR	Türkiye							
GBR	United Kingdom							
EU	OEL EU							
	TLV-ACGIH							
ACETONE								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	1200	500	2400 (C)	1000 (C)			
MAK	DEU	1200	500	2400	1000			
TLV	EST	1210	500					
VLEP	FRA	1210	500	2420	1000			
VLEP	ITA	1210	500					
NDS/NDSch	POL	600		1800				
TLV	ROU	1210	500					
MV	SVN	1210	500	2420	1000			
ESD	TUR	1210	500					
WEL	GBR	1210	500	3620	1500			
OEL	EU	1210	500					
TLV-ACGIH			250		500			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				10,6	mg/l			
Normal value in marine water				1,06	mg/l			
Normal value for fresh water sediment				30,4	mg/kg			
Normal value for marine water sediment				3,04	mg/kg			
Normal value for water, intermittent release				21	mg/l			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				33,3	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg				
Inhalation			VND	200 mg/m3	VND	2420 mg/m3	VND	1210 mg/m3
Skin			VND	62 mg/kg			VND	186 mg/kg
PROPANE								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.

Revision No: 4

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT

Revision Date: 01/02/2023

Printed on: 24/04/2025

Page No: 7/17

Replaced Revision: 3

AGW	DEU	1800	1000	7200	4000
MAK	DEU	1800	1000	7200	4000
TLV	EST	1800	1000		
NDS/NDSch	POL	1800			
TLV	ROU	1400	778	1800	1000
MV	SVN	1800	1000	7200	4000

XYLENE, MIXTURE OF ISOMERS

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		434	0	0	0

BUTANE

Threshold Limit Value

Type	Country	TWA/8h	STEL/15min	Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm
AGW	DEU	2400	1000	9600	4000
MAK	DEU	2400	1000	9600	4000
TLV	EST	4			peentolm
VLEP	FRA	1900	800		
NDS/NDSch	POL	1900		3000	
MV	SVN	2400	1000	9600	4000
WEL	GBR	1450	600	1810	750
WEL	GBR		4		RESP
TLV-ACGIH					1000

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.		Revision No: 4
		Revision Date: 01/02/2023
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT		Printed on: 24/04/2025
		Page No: 8/17
		Replaced Revision: 3
<p>SKIN PROTECTION</p> <p>Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.</p> <p>EYE PROTECTION</p> <p>Wear airtight protective goggles (see standard EN ISO 16321).</p> <p>RESPIRATORY PROTECTION</p> <p>Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).</p> <p>ENVIRONMENTAL EXPOSURE CONTROLS</p> <p>The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.</p>		
SECTION 9. Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Properties	Value	Information
Appearance	liquid	
Colour	according to the range	
Odour	of hydrocarbon aromatics	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
pH	not available	Reason for missing data:substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Kinematic viscosity	not available	
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not applicable	
Relative vapour density	not available	
Particle characteristics	not applicable	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes		
Information not available		
9.2.2. Other safety characteristics		

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT

VOC (Directive 2010/75/EU) 0
VOC (volatile carbon) 0,18 % - 1,32 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

10.4. Conditions to avoid

Avoid overheating.

ACETONE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ACETONE

Incompatible with: acids, oxidising substances.

10.6. Hazardous decomposition products

ACETONE

May develop: ketenes, irritant substances.

SECTION 11. Toxicological information

<p align="center">AKCALI BOYA VE KIMYA SANAYI TICARET A.S.</p>	<p>Revision No: 4 Revision Date: 01/02/2023</p>																				
<p align="center">083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT</p>	<p>Printed on: 24/04/2025 Page No: 10/17 Replaced Revision: 3</p>																				
<p>11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008</p> <p><u>Metabolism, toxicokinetics, mechanism of action and other information</u></p> <p>Information not available</p> <p><u>Information on likely routes of exposure</u></p> <p>Information not available</p> <p><u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u></p> <p>Information not available</p> <p><u>Interactive effects</u></p> <p>Information not available</p> <p>ACUTE TOXICITY</p> <table border="0"> <tr> <td>ATE (Inhalation - mists / powders) of the mixture:</td><td>3,8 mg/l</td></tr> <tr> <td>ATE (Oral) of the mixture:</td><td>Not classified (no significant component)</td></tr> <tr> <td>ATE (Dermal) of the mixture:</td><td>>2000 mg/kg</td></tr> </table> <p>ACETONE</p> <table border="0"> <tr> <td>LD50 (Dermal):</td><td>> 15800 mg/kg Coniglio</td></tr> <tr> <td>LD50 (Oral):</td><td>5800 mg/kg Ratto</td></tr> <tr> <td>LC50 (Inhalation vapours):</td><td>76 mg/l/4h Ratto</td></tr> </table> <p>XYLENE, MIXTURE OF ISOMERS</p> <table border="0"> <tr> <td>ATE (Dermal):</td><td>1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)</td></tr> <tr> <td>LD50 (Oral):</td><td>5000 mg/kg</td></tr> </table> <p>DIMETHYL CARBONATE</p> <table border="0"> <tr> <td>LD50 (Dermal):</td><td>> 5000 mg/kg Coniglio</td></tr> <tr> <td>LD50 (Oral):</td><td>13000 mg/kg Ratto</td></tr> </table> <p><u>SKIN CORROSION / IRRITATION</u></p> <p>Causes skin irritation</p> <p><u>SERIOUS EYE DAMAGE / IRRITATION</u></p> <p>Causes serious eye irritation</p> <p><u>RESPIRATORY OR SKIN SENSITISATION</u></p> <p>Does not meet the classification criteria for this hazard class</p> <p><u>Respiratory sensitization</u></p> <p>Information not available</p> <p><u>Skin sensitization</u></p>		ATE (Inhalation - mists / powders) of the mixture:	3,8 mg/l	ATE (Oral) of the mixture:	Not classified (no significant component)	ATE (Dermal) of the mixture:	>2000 mg/kg	LD50 (Dermal):	> 15800 mg/kg Coniglio	LD50 (Oral):	5800 mg/kg Ratto	LC50 (Inhalation vapours):	76 mg/l/4h Ratto	ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)	LD50 (Oral):	5000 mg/kg	LD50 (Dermal):	> 5000 mg/kg Coniglio	LD50 (Oral):	13000 mg/kg Ratto
ATE (Inhalation - mists / powders) of the mixture:	3,8 mg/l																				
ATE (Oral) of the mixture:	Not classified (no significant component)																				
ATE (Dermal) of the mixture:	>2000 mg/kg																				
LD50 (Dermal):	> 15800 mg/kg Coniglio																				
LD50 (Oral):	5800 mg/kg Ratto																				
LC50 (Inhalation vapours):	76 mg/l/4h Ratto																				
ATE (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)																				
LD50 (Oral):	5000 mg/kg																				
LD50 (Dermal):	> 5000 mg/kg Coniglio																				
LD50 (Oral):	13000 mg/kg Ratto																				

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.	Revision No: 4 Revision Date: 01/02/2023
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT	Printed on: 24/04/2025 Page No: 11/17 Replaced Revision: 3
<p>Information not available</p> <p><u>GERM CELL MUTAGENICITY</u></p> <p>Does not meet the classification criteria for this hazard class</p> <p><u>CARCINOGENICITY</u></p> <p>Does not meet the classification criteria for this hazard class</p> <p><u>REPRODUCTIVE TOXICITY</u></p> <p>Does not meet the classification criteria for this hazard class</p> <p><u>Adverse effects on sexual function and fertility</u></p> <p>Information not available</p> <p><u>Adverse effects on development of the offspring</u></p> <p>Information not available</p> <p><u>Effects on or via lactation</u></p> <p>Information not available</p> <p><u>STOT - SINGLE EXPOSURE</u></p> <p>May cause drowsiness or dizziness</p> <p><u>Target organs</u></p> <p>Information not available</p> <p><u>Route of exposure</u></p> <p>Information not available</p> <p><u>STOT - REPEATED EXPOSURE</u></p> <p>Does not meet the classification criteria for this hazard class</p> <p><u>Target organs</u></p> <p>Information not available</p> <p><u>Route of exposure</u></p> <p>Information not available</p> <p><u>ASPIRATION HAZARD</u></p> <p>Does not meet the classification criteria for this hazard class</p>	

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability**BUTANE**

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

PROPANE

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

ACETONE

Rapidly degradable

12.3. Bioaccumulative potential**BUTANE**

Partition coefficient: n-octanol/water 1,09

PROPANE

Partition coefficient: n-octanol/water 1,09

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.

Revision No: 4
Revision Date: 01/02/2023
Printed on: 24/04/2025
Page No: 13/17
Replaced Revision: 3

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT**12.7. Other adverse effects**

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.		Revision No: 4	
		Revision Date: 01/02/2023	
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT		Printed on: 24/04/2025	
		Page No: 14/17	
		Replaced Revision: 3	

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>	
Point	40

<u>Contained substance</u>	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor
The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.
All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.

Revision No: 4
Revision Date: 01/02/2023
Printed on: 24/04/2025
Page No: 15/17
Replaced Revision: 3

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Special finishes - All types.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ACETONE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Acute Tox. 4	Acute toxicity, category 4
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

AKCALI BOYA VE KIMYA SANAYI TICARET A.S.	Revision No: 4 Revision Date: 01/02/2023
083_K - AKCALI SPRAY SYNTHETIC PAINT SPECIAL EFFECT	Printed on: 24/04/2025 Page No: 17/17 Replaced Revision: 3
<p>Note for users:</p> <p>The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.</p> <p>This document must not be regarded as a guarantee on any specific product property.</p> <p>The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.</p> <p>Provide appointed staff with adequate training on how to use chemical products.</p> <p>CALCULATION METHODS FOR CLASSIFICATION</p> <p>Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.</p> <p>Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.</p> <p>Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.</p> <p>Changes to previous review:</p> <p>The following sections were modified:</p> <p>01 / 02 / 03 / 04 / 08 / 09 / 11 / 12 / 14 / 15 / 16.</p>	